

# Measurements and Metrics for Frequency, Time, and Packet Signals



**Lee Cosart**

lcosart@symmetricom.com

WSTS 2013

# Presentation Outline



---

- Introduction
  - TIE vs. PDV
  - Frequency vs. Time
  - Network vs. Equipment Measurements
  - Phase Detector and Packet Probe
- Metrics: Synchronization and Packet Analysis
  - TIE and PDV based metrics (G.810 and G.8260)
  - Packet selection processes and methods
  - Frequency transport PDV metrics
  - Time transport PDV metrics
- Measurement Case Studies
  - Networks
    - Time/frequency transport
  - Equipment
    - GM, BC, PRTC
- Conclusions

# Frequency signal “TIE” vs. “PDV”

- “TIE” (Single Point Measurement)


- Measurements are made at a single point – a single piece of equipment in a single location - a phase detector with reference - is needed



- “PDV” (Dual Point Measurement)

- Measurements are constructed from packets time-stamped at two points – in general two pieces of equipment, each with a reference, at two different locations – are needed



	Timestamp A	Timestamp B
F	1233166476.991204496	1233166476.991389744
R	1233166476.980521740	1233166476.980352932
F	1233166477.006829496	1233166477.007014512
R	1233166476.996147084	1233166476.995977932
F	1233166477.022454496	1233166477.022639568
R	1233166477.011771820	1233166477.011602932



# Time signal “Physical” vs. “Packet”

- “1 PPS” (Single Point Measurement)


- Measurements are made at a single point – a single piece of equipment in a single location - a phase detector with reference - is needed



- “Packet” (Dual Point Measurement)


- Measurements are constructed from packets time-stamped at two points – in general two pieces of equipment, each with a reference, at two different locations – are needed

	Timestamp A	Timestamp B
F	1286231440.883338640	1286231440.883338796
R	1286231441.506929352	1286231441.506929500
F	1286231441.883338640	1286231441.883338796
R	1286231442.506929352	1286231442.506929500
F	1286231442.883338640	1286231442.883338796
R	1286231443.506929352	1286231443.506929516




# TIE/PDV Measurements: Network vs. Equipment

Symmetricom TimeMonitor Analyzer (file=RB1DX1H.PAN)  
Phase deviation in units of time: Fs=984.0 MHz; Fo=2.0480000 MHz; 04/16/96:15:21:37




Network TIE

Symmetricom TimeMonitor Analyzer  
Phase deviation in units of time: Fs=499.4 MHz; Fo=10.000000 MHz; 2006/08/30 17:07:10  
Tahiti Phase; Samples: 49036; UUID: 00005501000A; Initial phase offset: 134.730 usec




Network PDV

Symmetricom TimeMonitor Analyzer (file=counter\_gps.dat)  
Phase deviation in units of time: Fs=58.80 MHz; Fo=1.0000000 Hz; \*7/12/2001 2:37:30 PM\*; \*7/15/2001 3:22:52 PM\*;  
HP 53132A; Test: 20; 58503A; Samples: 15400; Gate: 15 s; Ref ch1; TI/Time Data Only; TI 1->2;



Equipment TIE



Equipment PDV

## Passive Probe

vs.

## Active Probe



- (1) Hub or Ethernet Tap
- (2) IEEE 1588 Slave
- (3) Collection at Both Nodes

Passive probe sniffs packets: extra equipment required

- (1) No Hub or Ethernet Tap Needed
- (2) No IEEE 1588 Slave Needed
- (3) Collection at Probe Node Only

Active probe generates protocol: self-contained

## Network vs. Equipment PDV Measurement



# “TIE” Analysis vs. “PDV” Analysis

## “TIE” Analysis (G.810)

- Phase (TIE)
- Frequency accuracy
- Dynamic frequency
- MTIE
- TDEV

## “PDV” Analysis (G.8260)

- Phase (PDV)
- Histogram/PDF\*, CDF\*\*, statistics
- Dynamic statistics
- MATIE/MAFE
- TDEV/minTDEV/bandTDEV
- Two-way metrics: minTDISP etc.

- The importance of raw TIE/PDV:
  - Basis for frequency/statistical/MTIE/TDEV analysis
  - Timeline (degraded performance during times of high traffic?)
  - Measurement verification (jumps? offsets?)

\* *PDF = probability density function*

\*\* *CDF = cumulative distribution function*

- Traditional Clock Metrics

- ADEV, TDEV, MTIE
- Traditionally applied to oscillators, synchronization interfaces
- Also applied to lab packet equipment measurements

GM, BC

- Frequency Transport Packet Metrics

- minTDEV, MAFE, MATIE
- Applied to one-way packet delay data
- FPP/FPR/FPC (floor packet percentage/rate/count)


- Time Transport Packet Metrics

- minOffset, minTDISP
- Applied to two-way packet delay data
- Assesses link asymmetry

Packet  
Networks



# Analysis from Phase: Frequency




→  $-8.97 \cdot 10^{-14}$

## Frequency Accuracy

$$\omega = \frac{d\phi}{dt}$$

slope/linear: frequency offset  
curvature/quadratic: frequency drift


Symmetricom TimeMonitor Analyzer  
Fractional frequency offset: F=740.7 mHz; Fo=2.048 MHz; 08/15/08 07:55:45  
Holdover after 24 hours



1.5 E-9

## Point-by-point


Symmetricom TimeMonitor Analyzer (file=demo\_holdover.pan)  
Least square fit fractional frequency offset vs. time; N=100; 1/18/07; 19:44:26  
SSU holdover 4 days



1.2 E-11

## Segmented LSF

Symmetricom TimeMonitor Analyzer (file=demo\_holdover.pan)  
Fractional frequency offset: Overlap phase averaging; A=200; N=11056; Fs=32.26 mHz; Fo=2.048 MHz; 1/11  
SSU holdover 4 days




1.2 E-11

## Sliding Window Averaging

# Analysis from Phase: MTIE/TDEV

$$MTIE(S) = \max_{j=1}^{N-n+1} \left[ \max_{i=j}^{n+j-1} (x_i) - \min_{i=j}^{n+j-1} (x_i) \right]$$

MTIE is a peak detector  
MTIE detects frequency offset



$$\sigma_x(\tau) = TDEV(\tau) = \sqrt{\frac{1}{6} \left\langle \left[ \frac{1}{n} \sum_{i=1}^n x_{i+2n} - 2 \frac{1}{n} \sum_{i=1}^n x_{i+n} + \frac{1}{n} \sum_{i=1}^n x_i \right]^2 \right\rangle}$$

TDEV is a highly averaged “rms” type of calculation  
TDEV shows white, flicker, random walk noise processes  
TDEV does not show frequency offset

MTIE and TDEV analysis allows comparison to ATIS, Telcordia, ETSI, & ITU-T requirements

- Packet Selection Processes

**1) Pre-processed:** packet selection step prior to calculation

- Example: **TDEV**(PDV<sub>min</sub>) where PDV<sub>min</sub> is a new sequence based on minimum searches on the original PDV sequence

**2) Integrated:** packet selection integrated into calculation

- Example: **minTDEV**(PDV)

- Packet Selection Methods

– Minimum:  $x_{\min}(i) = \min[x_j] \text{ for } (i \leq j \leq i + n - 1)$


– Percentile:  $x'_{pct\_mean}(i) = \frac{1}{m} \sum_{j=0}^b x'_{j+i}$


– Band:  $x'_{band\_mean}(i) = \frac{1}{m} \sum_{j=a}^b x'_{j+i}$

– Cluster: 
$$x(n\tau_0) = \frac{\sum_{i=0}^{(K-1)} w((nK+i)\tau_p) \cdot \phi(n,i)}{\sum_{i=0}^{(K-1)} \phi(n,i)} \quad \phi(n,i) = \begin{cases} 1 & \text{for } |w(nK+i) - \alpha(n)| < \delta \\ 0 & \text{otherwise} \end{cases}$$


# Packet Selection Windows

- Windows
  - **Non-overlapping windows**  
(next window starts at prior window stop)
  - **Skip-overlapping windows**  
(windows overlap but starting points skip over N samples)
  - **Overlapping windows**  
(windows slide sample by sample)
- Packet Selection Approaches (e.g. selecting fastest packets)
  - Select X% fastest packets (e.g. 2%)
  - Select N fastest packets (e.g. 10 fastest packets in a window)
  - Select all packets faster than Y (e.g. all packets faster than 150μs)






**Figure I.3 – Pre-processed packet selection**



**Figure I.4 – Integrated packet selection**

G.8260(10)\_FI.4



**Metrics including pre-filtering**

FPC, FPR, FPP: Floor Packet Count/Rate/Percentage

**PDV metrics studying minimum floor delay packet population**

## Packet Delay Sequence

```
R,00162; 1223305830.478035356; 1223305830.474701511
F,00167; 1223305830.488078908; 1223305830.490552012
R,00163; 1223305830.492882604; 1223305830.489969511
F,00168; 1223305830.503473436; 1223305830.505803244
R,00164; 1223305830.508647148; 1223305830.505821031
F,00169; 1223305830.519029300; 1223305830.521302172
R,00165; 1223305830.524413852; 1223305830.521446071
F,00170; 1223305830.534542972; 1223305830.536801164
R,00166; 1223305830.540181132; 1223305830.537115991
F,00171; 1223305830.550229692; 1223305830.552551628
```

Packet  
Timestamps

Forward

#Start: 2009/10/06 15:10:30

0.0000,	2.473E-3
0.0155,	2.330E-3
0.0312,	2.273E-3
0.0467,	2.258E-3
0.0623,	2.322E-3


Reverse

#Start: 2009/10/06 15:10:30

0.0000,	3.334E-3
0.0153,	2.913E-3
0.0311,	2.826E-3
0.0467,	2.968E-3
0.0624,	3.065E-3


# Packet Delay Distribution

Symmetricom TimeMonitor Analyzer (file=xl\_1588\_pdv.tah)  
Phase deviation in units of time: Fs=500.0 MHz; Fo=10.000000 MHz; 2006/06/09 01:11:06  
XLI 1588 PDV Phase; Samples: 28561; UUID: 000055010016; Initial phase offset: 12.5420 usec



Packet Delay Sequence

Symmetricom TimeMonitor Analyzer  
Phase Deviation Histogram: Fs=500.0 MHz; Fo=10.00 MHz; 2006/06/09 01:11:06  
Tahiti Phase; Samples: 28561; UUID: 000055010016; Initial phase offset: 12.5420 usec




PDF

Minimum: 1.904297 usec	Mean: 96.71927 usec
Maximum: 275.2441 usec	Standard Deviation: 97.34 usec
Peak to Peak: 273.3 usec	Population: 28561
	Percentage: 100.0%

Statistics

Symmetricom TimeMonitor Analyzer (file=xl\_1588\_pdv.tah)  
Phase Deviation CDF: Fs=500.0 MHz; Fo=10.00 MHz; 2006/06/09 01:11:06  
XLI 1588 PDV Phase; Samples: 28561; UUID: 000055010016; Initial phase offset: 12.5420 usec




CDF

50pct: 37.65 us; 90pct: 245.5 us; 95pct: 261.9 us; 99pct: 272.3 us; 99.9pct: 274.5 us


# Tracked Packet Delay Statistics

Symmetricom TimeMonitor Analyzer (file=destination-2007\_09\_19-09\_39.cap)  
Phase deviation in units of time: Fs=16.66 Hz; Fo=10.000000 MHz; 2007/09/19 07:45:00  
XLi 1588 PDV Phase; Samples: 50185; Start: 5114; Threshold: 27.0000 us; UUID: 00A069012F09; Initial phase offset: 24.1950 usec




Raw packet delay appears relatively static over time

Symmetricom TimeMonitor Analyzer (file=pdv-2007\_09\_19-09\_39\_mean.pan)  
Phase Mean; Overlap: Tau=10s; A=167; N=50019; Phase deviation in units of time: Fs=16.66 Hz; Fo=10.000000 MHz; 2007/09/19 07:45:00



Mean vs. time shows cyclical ramping more clearly

Symmetricom TimeMonitor Analyzer (file=pdv-2007\_09\_19-09\_39\_stddev.pan)  
Phase Standard Deviation; Overlap: Tau=10s; A=167; N=50019; Phase deviation in units of time: Fs=16.66 Hz; Fo=10.000000 MHz; 2007/09/19 07:45:00



Standard deviation vs. time shows a quick ramp up to a flat peak

## minTDEV, bandTDEV, MATIE, MAFE

**TDEV**

$$\sigma_x(\tau) = TDEV(\tau) = \sqrt{\frac{1}{6} \left\langle \left[ \frac{1}{n} \sum_{i=1}^n x_{i+2n} - 2 \frac{1}{n} \sum_{i=1}^n x_{i+n} + \frac{1}{n} \sum_{i=1}^n x_i \right]^2 \right\rangle}$$

**minTDEV**

$$\sigma_{x\_min}(\tau) = \min TDEV(\tau) = \sqrt{\frac{1}{6} \left\langle [x_{min}(i+2n) - 2x_{min}(i+n) + x_{min}(i)]^2 \right\rangle} \quad x_{min}(i) = \min [x_j] \text{ for } (i \leq j \leq i+n-1)$$

**bandTDEV**

$$\sigma_{x\_band}(\tau) = bandTDEV(\tau) = \sqrt{\frac{1}{6} \left\langle [x'_{band\_mean}(i+2n) - 2x'_{band\_mean}(i+n) + x'_{band\_mean}(i)]^2 \right\rangle} \quad x'_{band\_mean}(i) = \frac{1}{m} \sum_{j=a}^b x'_{j+i}$$

1. TDEV is bandTDEV(0.0 to 1.0)
2. minTDEV is bandTDEV(0.0 to 0.0)
3. percentileTDEV is bandTDEV(0.0 to B) with B between 0.0 and 1.0

**MATIE**

$$MATIE(n\tau_0) \cong \max_{1 \leq k \leq N-2n+1} \frac{1}{n} \left| \sum_{i=k}^{n+k-1} (x_{i+n} - x_i) \right|, \quad n = 1, 2, \dots, \text{integer part } (N/2)$$

**MAFE**


$$MAFE(n\tau_0) = \frac{MATIE(n\tau_0)}{n\tau_0}$$

**minMAFE**

$$\min MAFE(n\tau_0) \cong \frac{\max_{1 \leq k \leq N-2n+1} \left| \sum_{i=k}^{n+k-1} (x_{min}(i+n) - x_{min}(i)) \right|}{n\tau_0} \quad \text{where } n = 1, 2, \dots, \text{integer part } (N/2) \text{ and where } x_{min}(i) = \min [x_j] \text{ for } (i \leq j \leq i+n-1)$$

# TDEV & minTDEV with Traffic


TDEV



Lower levels of noise with the application of a MINIMUM selection algorithm  
minTDEV at various traffic levels on a switch (0% to 50%) converge


Symmetricom TimeMonitor Analyzer (file=multilayer\_switch\_40percentSB60.txt)  
minTDEV; No. Avg=1; Fo=10.00 MHz; 2006/09/19; 15:28:30

minTDEV



## “PDV” measurement setup for time transport

- ✓ – Ideal setup - two packet timestampers with GPS reference so absolute latency can be measured as well as PDV over small to large areas
- ✓ – Alternative setup (lab) – frequency (or GPS) locked single shelf with two packet timestampers
- ✗ – Alternative setup (field) – frequency locked packet timestampers – PDV but not latency can be measured



# Metrics: Time Transport

## Forward Packet Delay Sequence

#Start: 2010/03/06 17:15:30

0.0000, 1.47E-6  
0.1000, 1.54E-6  
0.2000, 1.23E-6  
0.3000, 1.40E-6  
0.4000, 1.47E-6  
0.5000, 1.51E-6

## Reverse Packet Delay Sequence

#Start: 2010/03/06 17:15:30

0.0000, 1.11E-6  
0.1000, 1.09E-6  
0.2000, 1.12E-6  
0.3000, 1.13E-6  
0.4000, 1.22E-6  
0.5000, 1.05E-6

#Start: 2010/03/06 17:15:30

0.0000, 1.47E-6, 1.11E-6  
0.1000, 1.54E-6, 1.09E-6  
0.2000, 1.23E-6, 1.12E-6  
0.3000, 1.40E-6, 1.13E-6  
0.4000, 1.47E-6, 1.22E-6  
0.5000, 1.51E-6, 1.05E-6

Two-way  
Data Set

Constructing  $f'$  and  $r'$   
from  $f$  and  $r$  with a 3-  
sample time window

Time(s)	$f(\mu s)$	$r(\mu s)$	$f'(\mu s)$	$r'(\mu s)$
0.0	1.47	1.11		
0.1	1.54	1.09	1.23	1.09
0.2	1.23	1.12		
0.3	1.40	1.13		
0.4	1.47	1.22	1.40	1.05
0.5	1.51	1.05		

Minimum Search  
Sequence

## Packet Time Transport Metrics

*Normalized roundtrip:*  $r(n) = \left(\frac{1}{2}\right) \cdot [F(n) + R(n)]$

*Normalized offset:*  $\eta_2(n) = \left(\frac{1}{2}\right) \cdot [F(n) - R(n)]$

*minRoundtrip:*  $r'(n') = \left(\frac{1}{2}\right) \cdot [F'(n') + R'(n')]$

*minOffset:*  $\eta_2'(n') = \left(\frac{1}{2}\right) \cdot [F'(n') - R'(n')]$

*minTDISP (minimum time dispersion):* minOffset {y} plotted against minRoundtrip {x} as a scatter plot

*minOffset statistics:* minOffset statistic such as mean, standard deviation, or 95 percentile plotted as a function of time window tau


## minOffset Statistics

(Two-way minimum offset statistics vs. tau)

Symmetricom TimeMonitor Analyzer


Time stats plot in units of time; 2008/09/04; 16:55:05

minOffset mean (blue); minOffset stddev (red); minOffset 95% (magenta)




## Two-way MAFE (MAFE of minOffset)

Symmetricom TimeMonitor Analyzer (file=probe-2008\_09\_04--12\_54d.tpk)  
MAFE; Fo=10.00 MHz; Fs=100.6 MHz; 2008/09/04; 16:55:05




## Asymmetry in Wireless Backhaul

(Ethernet wireless backhaul asymmetry and IEEE 1588 slave 1PPS under these asymmetrical network conditions)




Min  
TDISP



1588  
Slave  
1 PPS  
vs.GPS


# Case Studies: Networks



Packet measurement

Packet data analysis:  
1PPB offset predicted


Symmetricon TimeMonitor Analyzer  
MTIE; Fo=2.048 MHz; Fs=499.8 mHz; 2009/09/04; 17:08:49  
G.823 1PPB mask




Sync measurement

1588 slave performance:  
1 PPB offset measured

## Metro Ethernet Network




## National Ethernet Network



Forward and reverse packet delay sequences with zooms into the respective floors and minTDISP


## Public Internet w/ Cable Modem Access (NTP probe)



Downstream maintains 8.7 msec minimum

Upstream minimum steps from 4.9 msec to 6.4 msec for 35 minutes

## Public Internet w/ ADSL Modem Access (NTP probe)




Downstream typically 9.0 msec minimum


Upstream typically 6.7 msec minimum, steps to 70 msec for 1 hour

Not shown: delays as much as several seconds


## Grandmaster Measurement Setup



# Case Studies: Grandmaster Clock




Raw unfiltered  
probe measurement



Overlay of filtered  
probe and 1PPS  
measurement


## Traditional Metrics Applied to Filtered Probe Measurement

Symmetricom TimeMonitor Analyzer; 2010/10/04; 22:30:40



MTIE


MTIE below G.811  
PRC mask



TDEV



TDEV below G.811  
PRC mask

## Boundary Clock Measurement Setup



## Boundary Clock Measurement: 3 Approaches


(1) Packet probe; (2) BC 1PPS; (3) Connected slave 1PPS



# Case Studies: Boundary Clocks


## Three boundary clocks from three vendors

Symmetricom TimeMonitor Analyzer (file=04749.dat)  
Phase deviation in units of time:  $F_s=499.9$  mHz;  $F_o=1.0000000$  Hz; \*4/9/2011 9:24:37 AM\*; \*4/10/2011 9:24:54 AM\*;  
HP 53132A; Test: 4749; BC 1PPS




BC Vendor #1

Symmetricom TimeMonitor Analyzer  
Phase deviation in units of time:  $F_s=499.9$  mHz;  $F_o=10.0000000$  MHz; \*10/19/2011 9:55:28 AM\*; \*10/24/2011 9:55:28 AM\*;  
HP 53132A; Test: 4874; BC 8 node TC14



BC Vendor #2

Symmetricom TimeMonitor Analyzer  
Phase deviation in units of time:  $F_s=249.9$  mHz;  $F_o=1.0000000$  Hz; \*4/28/2011 7:59:48 AM\*; \*6/3/2011 1:24:46 PM\*;  
HP 53132A; Test: 4809; BC 1PPS; Samples: 782198




BC Vendor #3

# Case Studies: Boundary Clocks

## Loaded 8-node network

Symmetricom TimeMonitor Analyzer


MTIE; Fo=1.000 Hz; Fs=498.9 mHz; 2011/04/09; 09:24:40



- A stable and accurate **time** reference is required. A cesium clock alone will not suffice.
- Possible candidates for such a reference:
  - National metrology lab reference
  - Carefully calibrated “golden” reference GPS receiver
- We need to understand both the accuracy and the stability characteristics of such a reference.
- We need to consider that both the reference and the PRTC under test may deliver different performance under conditions of constant temperature and varying temperature.

# “Golden” Reference GPS Receiver Stability


## Measurement Setup



Note: Measurements conducted at constant room temperature.

# “Golden” Receiver Stability Performance


Symmetricom TimeMonitor Analyzer  
Phase deviation in units of time:  $F_s=1.000\text{ Hz}$ ;  $F_o=1.0000000\text{ Hz}$ ; 2012/02/03; 15:35:09



Raw results vs. 3  
cesium clocks


Cesium 1 (blue):  $3.573\text{E-}13$   
Cesium 2 (red):  $1.579\text{E-}13$   
Cesium 3 (violet):  $-5.428\text{E-}13$

Symmetricom TimeMonitor Analyzer  
Phase deviation in units of time:  $F_s=1.000\text{ Hz}$ ;  $F_o=1.0000000\text{ Hz}$ ; 2012/02/03; 15:35:09



Results with  
respective cesium  
offsets removed


Symmetricom TimeMonitor Analyzer  
Phase deviation in units of time:  $F_s=1.000\text{ Hz}$ ;  $F_o=1.0000000\text{ Hz}$ ; 2012/02/03; 15:35:09



Zoom into 12 hour  
section of 10-day  
measurement


# “Golden” Receiver Stability Performance

Symmetricon TimeMonitor Analyzer  
Phase deviation in units of time;  $F_s=1.000\text{ Hz}$ ;  $F_o=1.0000000\text{ Hz}$ ; 2012/02/03; 15:35:09  
RefGPS (violet) and GM (gray) measured against cesium



“Golden” vs.  
conventional  
GPS receiver


Symmetricon TimeMonitor Analyzer  
Phase deviation in units of time;  $F_s=1.000\text{ Hz}$ ;  $F_o=1.0000000\text{ Hz}$ ; 2012/02/03; 15:35:09  
4 (green): Phase; Samples: 831170; HP 53132A; Avg 74/75/76 9.6 days; 2012/02/03; 15:35:09



Three “Golden”  
measurements  
averaged together


# “Golden” Receiver Stability Performance

Symmetricom TimeMonitor Analyzer  
MTIE; Fo=1.000 Hz; Fs=1.000 Hz; 2012/02/03; 15:35:09



“Golden” receiver  
MTIE performance

Symmetricom TimeMonitor Analyzer  
TDEV; Fo=1.000 Hz; Fs=1.000 Hz; 2012/02/03; 15:35:09



“Golden” receiver  
TDEV performance

- Types of measurements
  - Frequency, Time, and Packet Signals
  - “TIE” vs. Packet “PDV”
  - Network vs. Equipment
  - Packet probes: passive vs. active, PTP vs. NTP
- Clock and Packet Analysis
  - TIE analysis methods inform approach to PDV analysis
  - Stability metrics (1) Preprocessed or (2) Integrated packet selection
  - Frequency transport metrics
  - Time transport metrics
- Measurement Case Studies
  - Networks
    - Wireless backhaul: frequency and asymmetry
    - Metro/National Ethernet (PTP probe)
    - ADSL/Cable modem access (NTP probe)
  - Equipment
    - IEEE 1588 GM & BC (measurements on physical signal or packet signal)
    - PRTC: Four GPS receiver comparison (common antenna and common measurement reference)
    - PRTC: “Golden” receiver stability

# Thank You

---

**Lee Cosart**

Senior Technologist

[lcasart@symmetricom.com](mailto:lcasart@symmetricom.com)

Phone: +1-408-428-6950



Symmetricom, Inc.  
2300 Orchard Parkway  
San Jose, CA 95131-1017  
Tel: +1 408-428-7907  
Fax: +1 408-428-6960

[www.symmetricom.com](http://www.symmetricom.com)